

Seasons come and go.
Elements® endures.



Photo of actual Weathered Wood deck in Joplin, Missouri.

Redwood

Cape Cod Grey

Weathered Wood

Enjoy every season with the enduring beauty of Elements.®

Elements® composite decking provides a beautiful and durable option for enhancing your enjoyment of outdoor living spaces. This resilient extruded decking material offers the beauty of wood season after season. Elements decking comes with a 25-year limited warranty¹ and is available in three attractive color options:²

Decking Features & Benefits

- Beautiful wood grain look
- Available in three natural colors²
- Arched bottom design enhances board strength and stiffness
- Environmentally friendly. Recycled plastic and wood fiber content
- Low maintenance material saves time and money
- Coordinating skirting provides a professional finished look
- 25-year limited warranty¹ against rotting, splintering, splitting and termite damage
- Easy installation¹ with common tools and fasteners
- Colors naturally weather to a lighter shade of the same color²
- Building code approved: ATI-CCRR-0136

Decking Profiles

Nominal Size	Actual Size
1" x 6" x (12', 16' or 20')	15/16" x 57/32"
Skirting (12')	1/2" x 117/8"

All Tolerances +/- 1/16"

Decking Span Chart

Maximum recommended center-to-center spans with a minimum of three joists

Live Load	Residential Decks, Light Duty Decks	Commercial Decks, Docks, Boardwalks & Marinas
	100 psf	100 psf
1" x 6"	16"	16"



Elements® DockBoard

Elements® DockBoard is made with a special composite formulation to offer the level of performance needed in marine applications. The durable product provides slip resistance, eliminates splinters and has the strength to span 24" on center for residential and commercial applications. Available in an attractive Pier Grey color,² Elements DockBoard comes with a 25-year limited warranty from TAMKO.¹

- Strength to span 24" on center for residential and commercial applications
- Beautiful wood grain look
- Offered in an attractive Pier Grey color²
- No staining or painting required
- Available in 12-, 16- and 20-foot lengths for application versatility
- Comes with a 25-year limited warranty¹
- Easy installation¹ with common tools and fasteners
- Contains recycled material
- Color naturally weathers to a lighter shade of the same color²
- Building code approved: ATI-CCRR-0119



Photo of actual dock on Table Rock Lake, Missouri

Photo of actual dock on Grand Lake, Oklahoma



elementsdecking.com

DockBoard Profiles

Nominal Size	Actual Size
2" x 6" x (12', 16' or 20')	1.4" x 5 1/4"

All Tolerances +/- 1/16"

DockBoard Span Chart

Maximum recommended center-to-center spans with a minimum of three joists

Live Load	Residential Docks, Light Duty Docks	Commercial Docks, Boardwalks & Marinas		
	100 psf	100 psf	200 psf	250 psf
2" x 6"	24"	24"	22"	20"

TAMKO® Railing Systems Add the Ultimate Finishing Touch



Our coordinating railing systems lend themselves to endless customization options and creativity. They're made of durable composite materials that are just as easy to care for as ElementsDecking.

- **Designer Railing System** is a premium railing line offering distinguished styling. It features an extruded hand rail, universal top and bottom rail and patented oval baluster. Available in 6' straight rail and stair rail kits along with baluster kits and post sleeve kits to accommodate 36" or 42" railing heights. Injection molded post cap and post ring give the system the finishing details.
- **Tam-Rail® Railing System** delivers superior strength with the patented "Triple Layer" design. Features post mount kit for application flexibility, multi-angle bracket kit, square or colonial balusters and prepackaged straight and stair rail kits for quick and easy installation. For more details visit tam-rail.com.

Handling

For product care, handling and installation information visit elementsdecking.com or call 1-800-641-4691.

TAMKO Building Products, Inc.

P.O. Box 1404 • Joplin, MO 64802
Customer Service: 1-800-253-1401
Warranty Services: 1-800-441-7190

Distributed by:



¹ To obtain a copy of the limited warranty, the most current version of this sales sheet or the product installation instructions, visit elementsdecking.com or call 1-800-641-4691. Information included in this sales sheet was current at the time of printing.

² Representation of these colors is as accurate as our printing will permit. As with any composite product, color variations will occur. View several full-length pieces of material prior to final color selection and installation. Color of boards will usually weather to a lighter shade after several months of exposure to the environment. Color selection may vary across profiles.

Designer Railing System Profiles

Nominal Size	Actual Size
Post Cap & Ring	Fits Post Sleeve
4" x 4" x (116") Post Sleeve**	4 3/8" x 4 3/8"

6 FT Designer Rail Kit

70" Hand Rail, 70" Predrilled Universal Rails, 8 1/2" Crush Block, Hardware Pack

6 FT Designer Stair Rail Kit

74" Hand Rail, 74" Universal Rails, 8 1/2" Crush Block, Hardware Pack

Baluster Kit (Presized for 36" or 42" railing heights)

27" or 33" Predrilled Oval Balusters (13), Hardware Pack

Post Sleeve Kits** (38", 48" or 116" post sleeve)

4" x 4" x 38" or 48" Post Sleeve, Post Cap & Ring
4" x 4" x 116" Post Sleeve (Cap and Ring not included)

All Tolerances +/- 1/16"

**Post Sleeve is a nonstructural, ornamental accessory. Wood post is not included.

Tam-Rail Railing System Kits

Straight & Stair Rail Kits

36" rail kits available in nominal 6' and 8' lengths with your choice of square or colonial balusters. 42" rail kits available in nominal 6' lengths with square balusters.

Post Mount Kit

Post sleeve, pyramid post cap, post ring, post mount and hardware for use in either wood or masonry applications

Post Sleeves

Available in 38", 48" and 116" heights

Post Caps and Post Ring

New England cap and post ring, ball cap or pyramid cap available

Straight Rail Bracket Kit

For use with standard 6' and 8' straight railing kits

Stair Rail Bracket Kit

Accommodates stairs with a 30° to 32° slope

Multi-Angle Bracket Kit

For 22.5° and 45° angle applications and extended stair slope applications that range from 33° to 38°